

In the Abstract:

Please replace the Abstract with the following rewritten Abstract:

B1
~~An electrode drive circuit performs interlaced scanning, ensuring that the phases of the sustaining pulse in odd-numbered lines and even-numbered lines among L1 to L8 between surface discharge electrodes are the reverse of each other. With this, when either odd-numbered lines or even-numbered lines are displayed, the voltages applied between the electrodes of the undisplayed lines are at 0, eliminating the necessity for partitioning walls on the surface discharge electrodes. In surface discharge electrodes, X electrodes are provided on the two sides of a Y electrode and the area between the Y electrode and the X electrode on one side is assigned a display line at an odd-numbered frame, and the area between the Y electrode and the X electrode on the other side is assigned a display line in an even-numbered frame. Alternate areas between the surface discharge electrodes are assigned as blind lines and a discharge light emission in the blind lines is blocked or incident light to the blind lines from the outside is absorbed. Address electrodes are provided for each monochromatic pixel column and selectively connected with the pads above them, performing simultaneous selection of lines.~~

Method for driving a plasma display panel. At least one first discharge sustaining pulse is applied to a first pair of display electrodes, and at least one second discharge sustaining pulse is applied to an adjacent pair of display electrodes. The first and second discharge sustaining pulses are applied such that they are in the same phase as one

B1
Cont

another and/or such that a current in the first pair of display electrodes flows in the opposite
direction from a current in the adjacent pair of display electrodes.
